

LED FLUSH CIRCULAR PANELS



50,000 HOURS

3 YEAR WARRANTY

UP TO 91%
ENERGY SAVING

FLUSH MOUNT

EMERGENCY &
DIMMING AVAILABLE

Code	Diameter (mm)	Depth (mm)	Cut-Out (mm)	Wattage	Lumen	Colour temp	CRI	Operating Temp	Voltage	IP Rating	Replaces
ELED85/3/3000	90	13	75	3w	230	3000k	>80	-20°C - +50°C	100-240V AC	IP40	35W GU10
ELED85/3/4000	90	13	75	3w	250	4000k	>80	-20°C - +50°C	100-240V AC	IP40	35W GU10
ELED85/3/6000	90	13	75	3w	300	6000k	>80	-20°C - +50°C	100-240V AC	IP40	35W GU10
ELED120/6/3000	120	13	105	6w	505	3000k	>80	-20°C - +50°C	100-240V AC	IP40	50W GU10
ELED120/6/4000	120	13	105	6w	550	4000k	>80	-20°C - +50°C	100-240V AC	IP40	50W GU10
ELED120/6/6000	120	13	105	6w	600	6000k	>80	-20°C - +50°C	100-240V AC	IP40	50W GU10
ELED170/12/3000	170	13	160	12w	760	3000k	>80	-20°C - +50°C	100-240V AC	IP40	1 x 26W CFL
ELED170/12/4000	170	13	160	12w	800	4000k	>80	-20°C - +50°C	100-240V AC	IP40	1 x 26W CFL
ELED170/12/6000	170	13	160	12w	900	6000k	>80	-20°C - +50°C	100-240V AC	IP40	1 x 26W CFL
ELED225/20/3000	225	13	210	20w	1215	3000k	>80	-20°C - +50°C	100-240V AC	IP40	2 x 26W CFL
ELED225/20/4000	225	13	210	20w	1300	4000k	>80	-20°C - +50°C	100-240V AC	IP40	2 x 26W CFL
ELED225/20/6000	225	13	210	20w	1400	6000k	>80	-20°C - +50°C	100-240V AC	IP40	2 x 26W CFL
ELED300/25/3000	300	13	287	25w	1765	3000k	>80	-20°C - +50°C	100-240V AC	IP40	2 x 26W CFL
ELED300/25/4000	300	13	287	25w	1800	4000k	>80	-20°C - +50°C	100-240V AC	IP40	2 x 26W CFL
ELED300/25/6000	300	13	287	25w	2000	6000k	>80	-20°C - +50°C	100-240V AC	IP40	2 x 26W CFL