

ULTRA SLIM LINE RETROFIT LED PANELS



30,000 HOURS

3 YEAR WARRANTY

UP TO 72%
ENERGY SAVING

UNIVERSAL MOUNT
SURFACE OR FLUSH

EMERGENCY &
DIMMING AVAILABLE

Code	Diameter (mm)	Depth (mm)	Cut-Out (mm)	Wattage	Lumen	Colour temp	CRI	Operating Temp	Voltage	IP Rating
ELEDS6/3000	168	6.5	150	12w	1050	3000k	>80	-20°C - 45°C	200-240V AC	IP20
ELEDS6/4000	168	6.5	150	12w	1000	4000k	>80	-20°C - 45°C	200-240V AC	IP20
ELEDS6/6000	168	6.5	150	12w	1080	6000k	>80	-20°C - 45°C	200-240V AC	IP20
ELEDS8/3000	217	6.5	195	15w	1275	3000k	>80	-20°C - 45°C	200-240V AC	IP20
ELEDS8/4000	217	6.5	195	15w	1300	4000k	>80	-20°C - 45°C	200-240V AC	IP20
ELEDS8/6000	217	6.5	195	15w	1395	6000k	>80	-20°C - 45°C	200-240V AC	IP20
ELEDS12/3000	310	6.5	290	25w	2100	3000k	>80	-20°C - 45°C	200-240V AC	IP20
ELEDS12/4000	310	6.5	290	25w	2125	4000k	>80	-20°C - 45°C	200-240V AC	IP20
ELEDS12/6000	310	6.5	290	25w	2250	6000k	>80	-20°C - 45°C	200-240V AC	IP20